

# indoor



**3+6011**



**3+6012**




**3+6013**

## Specifications

| Code   | Power (W) | Voltage (V) | Lumen Efficiency (lm/W) | Colour Temperature (K) | CRI | IP Rating |
|--------|-----------|-------------|-------------------------|------------------------|-----|-----------|
| 3+6011 | 30W / 36W | 220V-240V   | 110lm/W                 | 3000K-5000K            | ≥90 | IP44/IP54 |
| 3+6012 | 30W / 36W | 220V-240V   | 110lm/W                 | 3000K-5000K            | ≥90 | IP44/IP54 |
| 3+6013 | 30W / 36W | 220V-240V   | 110lm/W                 | 3000K-5000K            | ≥90 | IP44/IP54 |



3+6011



3+6012  
3+6013



|                     |                               |
|---------------------|-------------------------------|
| LED                 | CREE LED                      |
| Beam Angle          | 40°                           |
| Tilt Rotation       | Fixed                         |
| Material            | Die-cast Aluminium            |
| Diffuser            | Clear Glass / Frosted         |
| Reflector           | Matt / Chrome / Mirror Finish |
| Colour              | Ivory White                   |
| Working Temperature | -20°C ~ +50°C                 |

IP65 and any body RAL colour is available on demand

**CREE** 

**CE**  **ERP**  **RoHS compliant**

